

CLAIMS

What is claimed is:

1. A digital cross connect comprising:
plural switching stages, each stage having plural switches receiving
5 plural frames of time multiplexed input data and switching the data in time and
space; and
configuration storage at each switch storing a time/space configuration
for the switch, all switches switching configuration to the stored time/space
10 configuration in frame synchronization at the start of synchronized data frames
by synchronizing switches of successive stages to a configuration select signal
propagated from at least one switch of an input stage.
2. A cross connect as claimed in claim 1 wherein the configuration select signal is
embedded within a frame of data.
3. A cross connect as claimed in claim 2 wherein the configuration select signal is
15 embedded in an A1 byte of a SONET frame.
4. A cross connect as claimed in claim 3 wherein the configuration select signal is
embedded in the fourth A1 byte of an STS-48 frame.
5. A cross connect as claimed in claim 1 wherein configuration switching is
initiated by a prepare-to-switch signal propagated from a master switch to all
20 switches of an output stage and the input stage, the at least one switch of the
input stage then propagating the configuration select signal.

6. A cross connect as claimed in claim 5 wherein the prepare-to-switch signal is embedded within a frame of data.
7. A cross connect as claimed in claim 6 wherein the prepare-to-switch signal is embedded in an A1 byte of a SONET frame.
- 5 8. A cross connect as claimed in claim 7 wherein the prepare-to-switch signal is embedded in the second and third bytes of an STS-48 frame.
9. A cross connect as claimed in claim 5 wherein switches of the first and last stages are on common chips.
- 10 10. A cross connect as claimed in claim 9 wherein the common chips of the first and last stages support respective framing time bases for the first and last stages.
11. A cross connect as claimed in claim 9 wherein connections from the first stage expand in space from input connections, and connections to the last stage concentrate in space to output connections.
12. A cross connect as claimed in claim 11 wherein chips of a common design support the switches of all stages.
- 15 13. A cross connect as claimed in claim 5 wherein the prepare-to-switch signal from the master switch is in a signal which is qualified to distinguish the signal from the master switch from signals from other switches.
14. A cross connect as claimed in claim 13 wherein the qualifier and the configuration data are embedded in A1 bytes of a SONET frame.
- 20

03761533 011601

15. A cross connect as claimed in claim 5 wherein the master switch is in a middle stage.
16. A cross connect as claimed in claim 1 wherein each switch comprises a time slot interchanger associated with each input and output port thereof and a space switch.
- 5
17. A method of cross connecting digital data comprising:
- providing plural switching stages, each stage having plural switches receiving plural frames of time multiplexed input data and switching the data in time and in space;
- 10 providing configuration storage at each switch to store a time/space configuration for the switch;
- propagating a configuration select signal from at least one input switch of an input stage to successive stages; and
- switching configuration of the switches to the stored time/space configurations in frame synchronization at the start of synchronized data frames by synchronizing switches of the successive stages to the configuration select signal.
- 15
18. A method as claimed in claim 17 wherein the configuration select signal is embedded within a frame of data.
- 20 19. A method as claimed in claim 18 wherein the configuration select signal is embedded in an A1 byte of a SONET frame.
20. A method as claimed in claim 19 wherein the configuration select signal is embedded in the fourth A1 byte of an STS-48 frame.

20250103001001

21. A method as claimed in claim 17 wherein configuration switching is initiated by a prepare-to-switch signal propagated from a master switch to all switches of an output stage and the input stage, the at least one switch of the input stage then propagating the configuration select signal.
- 5 22. A method as claimed in claim 21 wherein the prepare-to-switch signal is embedded within a frame of data.
23. A method as claimed in claim 22 wherein the prepare-to-switch signal is embedded in an A1 byte of a SONET frame.
24. A method as claimed in claim 23 wherein the prepare-to-switch signal is
10 embedded in the second and third bytes of an STS-48 frame.
25. A method as claimed in claim 21 wherein switches of the first and last stages are on common chips.
26. A method as claimed in claim 25 further comprising switching the data of the
15 first and last stages in synchronization with respective framing time bases for the first and last stages.
27. A method as claimed in claim 25 wherein the frames from the first stage expand in space from input connections, and frames to the last stage concentrate in space to output connections.
28. A method as claimed in claim 27 wherein chips of a common design support the
20 switches of all stages.

For Office Use Only

29. A method as claimed in claim 21 wherein the prepare-to-switch signal from the master switch is in a signal which is qualified to distinguish the master signal from signals from other switches.
30. A method as claimed in claim 29 wherein the qualifier and the configuration data are embedded in A1 bytes of a SONET frame.
31. A method as claimed in claim 21 wherein the master switch is in a middle stage.
32. A method as claimed in claim 17 wherein each switch comprises a time slot interchanger associated with each input and output port thereof and a space switch.
33. A digital cross connect comprising:
plural switching stages, each stage having plural switching means for receiving plural frames of time multiplexed input data and switching the data in time and space;
configuration storage means at each switch for storing a time/space configuration for the switch; and
means for switching configuration of the switches to the stored time/space configuration in synchronization with a configuration select signal propagated from at least one input switching means of an input stage.
34. A digital cross connect comprising:
plural switching stages, each stage having plural switches, each comprising a time slot interchanger associated with each input and output port thereof and a space switch, each switch receiving plural frames of time multiplexed input data and switching the data in time and space; and

configuration storage at each switch storing a time/space configuration for the switch, all switches switching configuration to the stored time/space configuration in frame synchronization at the start of synchronized data frames.

35. A method of cross connecting digital data comprising:

5 providing plural switching stages, each stage having plural switches, each comprising a time slot interchanger associated with each input and output port thereof and a space switch, each switch receiving plural frames of time multiplexed input data and switching the data in time and in space;

10 providing configuration storage at each switch to store a time/space configuration for the switch; and
 switching configuration of the switches to the stored time/space configurations in frame synchronization at the start of synchronized data frames by synchronizing switches of the successive stages to the configuration select signal.

- 15 36. A digital cross connect comprising:

 plural switching stages, each stage having plural switching means, each comprising a time slot interchanger associated with each input and output port thereof and a space switch, for receiving plural frames of time multiplexed input data and switching the data in time and space;

20 configuration storage means at each switch for storing a time/space configuration for the switch; and

 means for switching configuration of the switches to the stored time/space configuration in frame synchronization at the start of synchronized data frames.

- 25 37. A digital cross connect comprising plural switching stages, each stage having plural switches on plural chips receiving plural frames of time multiplexed input

2025 RELEASE UNDER E.O. 14176

data and switching the data in time and space, switches of different stages being on common chips supporting respective framing time bases for the different stages.

38. A cross connect as claimed in claim 37 wherein connections from a first stage
5 expand in space from input connections and connections to a second stage
concentrate in space to output connections.
39. A cross connect as claimed in claim 37 wherein the different stages are first and
final stages of the plural switching stages.
40. A cross connect as claimed in claim 39 wherein connections from the first stage
10 expand in space from input connections, and connections to the final stage
concentrate in space to output connections.
41. A switch circuit on an integrated circuit chip comprising:
switch circuitry receiving plural frames of time multiplexed input data
and switching the data in time and space;
15 a first frame counter to which a first portion of the plural frames of time
multiplexed input data is synchronized; and
a second frame counter to which a second portion of the plural frames of
time multiplexed input data is synchronized.
42. A switching circuit as claimed in claim 41 wherein connections expand in space
20 from input connections to the first portion, and connections concentrate in space
to output connections of the second portion.

09761336 041604

43. Switching circuitry as claimed in claim 41 which responds to a prepare-to-switch signal received with the second portion to initiate a configuration select signal propagated with the first portion.
44. Switching circuitry as claimed in claim 43 wherein the configuration select
5 signal is embedded within a frame of data.
45. Switching circuitry as claimed in claim 44 wherein the configuration select signal is embedded in an A1 byte of a SONET frame.
46. Switching circuitry as claimed in claim 45 wherein the configuration select signal is embedded in the fourth A1 byte of an STS-48 frame.
- 10 47. Switching circuitry as claimed in claim 44 wherein the prepare-to-switch signal is embedded within a frame of data.
48. Switching circuitry as claimed in claim 47 wherein the configuration select signal and the prepare to switch signal are embedded within A1 bytes of a SONET frame.
- 15 49. Switching circuitry as claimed in claim 43 wherein the prepare-to-switch signal is embedded within a frame of data.
50. Switching circuitry as claimed in claim 49 wherein the prepare-to-switch signal is embedded in an A1 byte of a SONET frame.
51. Switching circuitry as claimed in claim 50 wherein the prepare-to-switch signal
20 is embedded in the second and third bytes of an STS-48 frame.

US 2005/0160000 A1

52. Switching circuitry as claimed in claim 41 wherein input frames to and output frames from the switch circuitry are programmably assignable to the first and second portions.

US 7,645,338 B1